

Kolibri

Kolibri applications	19
Kolibri dimensions	20
Kolibri types	21
Kolibri sizes	22
Kolibri height 10	23
Kolibri height 15	24
Kolibri height 22	26
Kolibri height 30	28
Kolibri height 40	33
Kolibri height 50	35
Kolibri height 65	37
Kolibri parts	39
Kolibri assembly	40
Kolibri flange connect.	42
Kolibri part numbers	44



closed + open

Kolibri CHARACTERISTICS

The inexpensive energy chain for light-weight applications. The patented opening offers high rigid torsion behaviour and comfortable handling in one.

easy access by flap stays
extremely rigid and wear resistant
unique separation with the pinch stay
smallest dimensions

All ekd plastic energy chains are equipped with integrated connectors. Additional mounting parts are not needed.

Dimensions

bending radii:	15	to	400 mm
inner height:	7	to	50 mm
inner width:	7	to	195 mm
weight:	0.06	to	2.7 kg/m

Travel distance

The maximum travel distance is given by the arrangement and the load (weight of the lines). At normal arrangements the maximum travel distance is double the free carrying length. Support rollers or similar equipment may exceed this value.

In gliding arrangements travel distances up to 100 m are possible (according to the application). For longer travels see chapter on design guidelines.

Travel speed

There are no limits for the travel speed in general. But with gliding arrangements application specific influences have to be taken into account.

Acceleration



There are no limits for the accelerations, in general. Limits may occur through the tensile stresses at high line weights.



Temperatue

Long term temperature limits are between -20°C and 100°C.

Special variants



ELTOLA	... silent running
ATEX	... EX-protection
ESD	... antistatic
V-0	... self extinguishing





robotics, handling,
transportation, paper production,
textile industries, water plants





Kolibri			pitch			dimensions							weight
c . d .type	prev. name			a	b	c	d	g	h	i ¹⁾	j ¹⁾	t ²⁾	kg/m
10.012.4	00.3		15	Ø7		10	12	12	3	-	-	-	0.05
13.023.4			20	9	14	13	23	19	3	-	-	-	0.12
15.015.3 .4	0	0.3	20	Ø10		15	15	15	4	-	-	-	0.15
15.036.5		02.5	18	10	25	15	36	30	4	-	-	-	0.30
15.037.3			20	10	24	15	37	30	4	-	-	-	0.30
15.051.0	03		20	10	39	15	51	44	4	-	-	-	0.35
22.025.4	04.3		30	17	15	22	25	19,4	4	-	-	-	0.20
22.038.0	05.0		26	17	27	22	38	32.5	4	8	10	2	0.34
22.048.0	06		30	17	36	22	48	41	4	13	10	2	0.37
22.060.5		07.5	26	16	48	22	60	54	4	9,5	10	2	0.54
30.030.3	1		40	24	18	30	30	23	4	-	-	-	0.50
30.060.3	2		40	24	48	30	60	53	4	-	-	-	0.60
30.050.0 .1 .5	10.0	10.5	35	23	34	30	50	40	5	9,5	5	3 ²⁾	0.54
30.060.0 .1	11.0		35	23	44	30	60	50	5	9,5	5	3	0.61
30.080.0 .1 .2 .4 .5	12.0	12.5	35	23	64	30	80	70	5	9,5	5	3 ²⁾	0.65
30.095.0 .1	13.0		35	23	79	30	95	85	5	12	5	3	0.75
30.125.0 .1	14.0		35	23	109	30	125	115	5	12	5	3	0.87
40.062.2 .5		15.5	45	29	48	40	62	54	5	8	10	4	0.91
40.075.2 .6			45	29	60	40	75	67	5	8	10	4	1.05
40.112.7			37	31	55 ...	100		127	5	5	5	3	1,05
50.065.0 .5	21.0	21.5	55	40	48	50	65	55	6	9 ³⁾	9 ³⁾	2	1.30
50.095.0 .1 .2 .5	19.0	19.5	55	40	78	50	95	85	6	6,5 ³⁾	5 ³⁾	2	1.35
50.125.0 .1	22.0		55	40	108	50	125	115	6	6,5	5	3	1.52
50.150.0 .1 .5	20.0	20.5	55	40	133	50	150	140	6	6,5 ³⁾	5 ³⁾	3	1.90
65.095.1 .5		24.5	70	50	77	65	95	85	6	13,5	10	4	2.20
65.135.1 .5		25.5	70	50	117	65	135	125	6	13,5	10	4	2.60

1) not Kolibri *.2

2) for Kolibri *.2 is t=4 for Kolibri *.5 is t=2

3) for Kolibri*.5 is i=9,5 and j=10

Kolibri DIMENSIONS

Kolibri 00.000.0

standard type

flap open bars in inner radius
separable with pinch stay
integrated connector



Kolibri 00.000.1

openable in outer radius

flap open bars in outer radius
separable with pinch stay
integrated connector



Kolibri 00.000.2

rigid version

flap open bars in inner radius
separable with PZ
integrated connector



Kolibri 00.000.6
equal .2
flap open bars
in outer radius

Kolibri 00.000.3

one part chain links

not openable
not separable
integrated connector



Kolibri 00.000.4

film stay

film stay in inner radius
not separable
(integrated connector)



Kolibri 00.000.5

closed type

flap open covers in outer radius
separable with pinch stay
integrated connector



Kolibri

c . d . type	prev. name		radius										Kolibri 00.000.7 telescopic type PKK stays in inner radius separable via Pz separate connectors	
10.012.4	00.3		15	30	50									
13.023.4			17,5	35										
15.015.3 .4	0	0.3	17,5 ²⁾	20	30									
15.036.5		02.5		30	50									
15.037.3				24	30									
15.051.0	03			20	30									
22.025.4	04.3			35	70	100								
22.038.0	05.0			35	50	60	70	100						
22.048.0	06			35	70									
22.060.5		07.5			50	70	100							
30.030.3	1			40		100								200
30.060.3	2			40		100	150	200						
30.050.0 .1 .5	10.0	10.5		40 ¹⁾	60	75	100	150	200					
30.060.0 .1	11.0			40	50	75	100	150	200					
30.080.0 .1 .2 .4 .5	12.0	12.5		40 ¹⁾	60 ⁴⁾	75	100	150	200					
30.095.0 .1	13.0			40		75	100	125	150	200				
30.125.0 .1	14.0			40		75	100	150	200					
40.062 .2 .5		15.5			60 ¹⁾	75	100	150	200					
40.075.2 .6					60	75	100	150	200					
40.112.7					55									
50.065.0 .5	21.0	21.5			75 ¹⁾	100	125 ¹⁾	150	200	250				
50.095.0 .1 .2 .5	19.0	19.5			75 ¹⁾	100	125 ¹⁾	150	175 ¹⁾	200	250			
50.125.0 .1	22.0				75	100	125	150	200	250				
50.150.0 .1 .5	20.0	20.5			75 ¹⁾	100		150	200	250				
65.095.1 .5	24.1	24.5					125	150	200	300				
65.135.1 .5		25.5					125	150	200	300 ³⁾				
65.195.1 .5		27.5					125	150	200	300				

1) not Kolibri xx.xxx.5

2) only Kolibri 15.015.3

3) additional R400

4) only Kolibri 30.080.5

height 10




height 13




height 15




height 22




height 30




height 40



height 50




height 65



Kolibri HEIGHT 10

inner height 7 up to 8, inner width 7 up to 14




Kolibri 10.012.4

one part link
film stay in inner radius
integrated connector or separate connectors
space (axb): **Ø7 not separable**
bend radius: 15 / 30 / 50
weight: 0,05 kg/m
free carrying length: 0.4 m at 0.3 kg/m load
pitch: 15

order example:

Kolibri 10.012.4 / 50 x 1005

type / radius x length




Kolibri 13.023.4

one part link
fether stay in inner radius
integrated connector
space (axb): **8x14 not separable**
bend radius: 17,5 / 35 / 55 / 80 / 100
weight: 0,12 kg/m
free carrying length: 0,8 m at 0.5 kg/m load
pitch: 20


order example:

Kolibri 10.012.4 / 50 x 1005

type / radius x length



fether stay long
max. Ø5mm



fether stay short
Max. Ø8.5mm



Snap

(see page 26,32,39,41)





Kolibri HEIGHT 15

inner height 10, inner width 10 to 39

Kolibri 15.015.3

one part chain link
not openable
connector as separate part (part.no. 0700)
space (axb): $\varnothing 10$ not separable
bend radius: 17.5 / 20 / 30
weight: 0.15 kg/m
free carrying length: 0.9m at 0.9 kg/m load
pitch: 20

order example:

Kolibri 15.015.3 / 30 x 1000

type / radius x length




Kolibri 15.015.4

one part chain link
film-stay in inner radius
connector as separate part (see Kolibri 15.015.3)
space (axb): $\varnothing 10$ not separable
bend radius: 20 / 30
weight: 0.15 kg/m
free carrying length: 0.9 m at 0.9 kg/m load
pitch: 20

order example:

Kolibri 15.015.4 / 30 x 1000

type / radius x length



Kolibri 15.036.5

closed type
flap covers in outer radius
integrated connectors
space (axb): 10 x 25 not separable
bend radius: 30 / 50
weight: 0.3 kg/m
free carrying length: 0.9m at 0.9 kg/m load
pitch: 18

order example:

Kolibri 15.036.5 / 30 x 1008

type / radius x length



Kolibri HEIGHT 15

inner height 10, inner width 10 to 39



ekd gelenkroh
energy drag chains

Kolibri 15.037.3

one part chain link

not openable, closed in outer radius

integrated connectors

Space (axb): 10 x 24 not separable
bend radius: 24, 30
weight: 0.3 kg/m
free carrying length: 0.9 at 0.9 kg/m load
pitch: 20

order example:

Kolibri 15.037.3 / 30 x 1000

type / radius x length



Kolibri 15.051.0

standard type

flap stay in inner radius


integrated connectors

space (axb): 10 x 39 not separable
bend radius: 20 / 30
weight: 0.35 kg/m
free carrying length: 0.9 m at 0.9 kg/m load
pitch: 20

order example:

Kolibri 15.051.0 / 30 x 1000

type / radius x length





Kolibri HEIGHT 22

inner height 16 to 22, inner width 15 to 48

Kolibri 22.025.4

one part chain link

film stay

integrated connectors

space (axb): 17 x 15 not separable

bend radius: 35 / 70 / 100

weight: 0.20 kg/m

free carrying length: 1.3 m at 1.5 kg/m load

pitch: 30

order example:

Kolibri 22.025.4 / 35 x 1020

type / radius x length



Kolibri 22.038.0

standard type

flap stay in inner radius

integrated connectors

space (axb): 17 x 27 separable (PZ ANr.1688)

bend radius: 35 / 50 / 70 / 100

weight: 0.34 kg/m


free carrying length: 1.5 m at 1.0 kg/m load

pitch: 26

order example:

Kolibri 22.038.0 / 35 x 1040

type / radius x length





Kolibri 22.038.0 Snap

Kolibri 22.038.0 is available with Snap connectotr:

Quick and toolless assembly of the energy chain with only one clock.

Please contact the ekd gelenkrohr design department.

Assembly example:



Kolibri HEIGHT 22

inner height 16 to 22, inner width 15 to 48

max. 14-20

ekd gelenkrohr
energy drag chains

Kolibri 22.048.0

open type

flap stay in inner radius

integrated connectors

space (axb): 17 x 36 not separable

bend radius: 35 / 70

weight: 0.37 kg/m

free carrying length: 1.3 m at 1.5 kg/m load

pitch: 30

order example:

Kolibri 22.048.0 / 35 x 1200

type / radius x length



Kolibri 22.060.5

closed type

flap stay in outer radius

integrated connectors

space (axb): 16 x 48 separable (PZ ANr.1294)

bend radius: 50 / 70 / 100

weight: 0.54 kg/m

free carrying length: 1.3 m at 1.5 kg/m load

pitch: 26

order example:

Kolibri 22.060.5 / 100 x 1014

type / radius x length





Kolibri HEIGHT 30

inner height 23 to 24, inner width 18 to 109

Kolibri 30.030.3

one part chain link
not openable
integrated connectors

space (axb): 24 x 18 not separable
bend radius: 40 / 100 / 200
weight: 0.50 kg/m
free carrying length: 1.5 m at 2.0 kg/m load
pitch: 40

order example:

Kolibri 30.030.0 / 100 x 1200

type / radius x length



Kolibri 30.050.0


standard type
flap stay in inner radius
integrated connectors

space (axb): 23 x 34 separable (PZ ANr.1258)
bend radius: 40 / 60 / 75 / 100 / 150 / 200
weight: 0.54 kg/m
free carrying length: 1.5 m at 2.0 kg/m load
pitch: 35

order example:

Kolibri 30.050.0 / 100 x 1225

type / radius x length



Kolibri 30.050.1


open type
flap stay in outer radius
integrated connectors

space (axb): 23 x 34 separable (PZ ANr.1258)
bend radius: 40 / 60 / 75 / 100 / 150 / 200
weight: 0.54 kg/m
free carrying length: 1.5 m at 2.0 kg/m load
pitch: 35

order example:

Kolibri 30.050.1 / 100 x 1225

type / radius x length



Kolibri 30.050.5

closed type
flap covers in outer radius
integrated connectors

space (axb): 23 x 34 separable (PZ ANr.1017)
bend radius: 60 / 75 / 100 / 150 / 200
weight: 0.58 kg/m
free carrying length: 1.5 m at 2.0 kg/m load
pitch: 35

order example:


Kolibri 30.050.5 / 100 x 1225

type / radius x length



Kolibri HEIGHT 30

inner height 23 to 24, inner width 18 to 109



Kolibri 30.060.0


standard type
flap stay in inner radius
integrated connectors

space (axb): 23 x 44 separable (PZ ANr.1258)
bend radius: 40 / 50 / 75 / 100 / 150 / 200
weight: 0.61 kg/m
free carrying length: 1.5 m at 2.0 kg/m load
pitch: 35

order example:

Kolibri 30.060.0 / 100 x 1225

type / radius x length



Kolibri 30.060.1


open type
flap stay in outer radius
integrated connectors

space (axb): 23 x 44 separable (PZ ANr.1258)
bend radius: 40 / 50 / 75 / 100 / 150 / 200
weight: 0.61 kg/m
free carrying length: 1.5 m at 2.0 kg/m load
pitch: 35

order example:

Kolibri 30.060.1 / 100 x 1225

type / radius x length



Kolibri 30.060.3

open type
not openable
integrated connectors

space (axb): 24 x 48
bend radius: 40 / 100 / 150 / 200
weight: 0.60 kg/m
free carrying length: 1.5 m at 2.0 kg/m load
pitch: 40

order example:

Kolibri 30.080.1 / 100 x 1225

type / radius x length



Kolibri 30.080.0


standard type
flap stay in inner radius
integrated connectors

space (axb): 23 x 64 separable (PZ ANr.1258)
bend radius: 40 / 75 / 100 / 150 / 200
weight: 0.65 kg/m
free carrying length: 1.5 m at 2.0 kg/m load
pitch: 35

order example:

Kolibri 30.080.0 / 100 x 1225

type / radius x length





Kolibri HEIGHT 30

inner height 23 to 24, inner width 18 to 109

Kolibri 30.080.1

standard type
flap stay in outer radius
integrated connectors

space (axb): 23 x 64 separable (PZ ANr.1258)
bend radius: 40 / 75 / 100 / 150 / 200
weight: 0.65 kg/m
free carrying length: 1.5 m at 2.0 kg/m load
pitch: 35

order example:

Kolibri 30.080.0 / 100 x 1225

type / radius x length

Kolibri 30.080.2

rigid type
flap stay in inner radius
integrated connectors

space (axb): 21 x 64 not separable
bend radius: 40 / 75 / 100 / 150 / 200
weight: 0.7 kg/m
free carrying length: 1.5 m at 2.0 kg/m load
pitch: 35

order example:

Kolibri 30.080.2 / 100 x 1225

type / radius x length

Kolibri 30.080.4

one part chain link
lining without assembly
integrated connectors

space (axb): 21 x 64 not separable
bend radius: 40 / 75 / 100 / 150 / 200
weight: 0.65 kg/m
free carrying length: 1.5 m at 2.0 kg/m load
pitch: 35

order example:

Kolibri 30.080.4 / 100 x 1225

type / radius x length

Kolibri 30.080.5

closed type
flap covers in outer radius
integrated connectors

space (axb): 23 x 64 separable (PZ ANr.1017)
bend radius: 60 / 75 / 100 / 150 / 200
weight: 0.7 kg/m
free carrying length: 1.5 m at 2.0 kg/m load
pitch: 35


order example:

Kolibri 30.080.5 / 100 x 1225

type / radius x length

Kolibri HEIGHT 30

inner height 23 to 24, inner width 18 to 109



Kolibri 30.095.0

standard type

flap stays in inner radius

integrated connectors

space (axb): 23 x 79 separable (PZ ANr.1258)

bend radius: 40 / 75 / 100 / 125 / 150 / 200

weight: 0.75 kg/m


free carrying length: 1.5 m at 2.0 kg/m load

pitch: 35

order example:

Kolibri 30.095.0 / 100 x 1225

type / radius x length



Kolibri 30.095.1

open type

flap stays in outer radius

integrated connectors

space (axb): 23 x 79 separable (PZ ANr.1258)

bend radius: 40 / 75 / 100 / 125 / 150 / 200

weight: 0.75 kg/m

free carrying length: 1.5 m at 2.0 kg/m load

pitch: 35

order example:

Kolibri 30.095.1 / 100 x 1225

type / radius x length



Snap

toolless assembly
of the chain



Kolibri HEIGHT 30

inner height 23 to 24, inner width 18 to 109

Kolibri 30.125.0

standard type
flap stay in inner radius
integrated connectors

space (axb): 23 x 109 separable (PZ ANr.1258)
bend radius: 40 / 75 / 100 / 150 / 200
weight: 0.87 kg/m
free carrying: 1.5 m at 2.0 kg/m load
pitch: 35

order example:

Kolibri 30.125.0 / 100 x 1225

type / radius x length

Kolibri 30.125.1

open type
flap stay in outer radius
integrated connectors

space (axb): 23 x 109 separable (PZ ANr.1258)
bend radius: 40 / 75 / 100 / 150 / 200
weight: 0.87 kg/m
free carrying: 1.5 m at 2.0 kg/m load
pitch: 35

order example:



Kolibri 30.125.1 / 100 x 1225

type / radius x length

Kolibri with Snap


Type Kolibri allows using the Snap connector:
Fast and toolless assembly of the energy chain with only one click.
Please contact ekd gelenkrohr technic during your Planing phase.

assembly example:



Kolibri HEIGHT 40

inner height 31, inner width 48 to 60



Kolibri 40.062.2

rigid type

flap stay in inner radius

integrated connectors

space (axb): 29 x 48 separable (PZ ANr.1521)

bend radius: 60 / 75 / 100 / 150 / 200

weight: 0.91 kg/m


free carrying length: 2.0 m at 1.0 kg/m load

pitch: 45

order example:

Kolibri 40.062.2 / 100 x 1260

type / radius x length



Kolibri 40.062.5

closed type

flap covers in outer radius

integrated connectors

space (axb): 29 x 48 separable (PZ ANr.1268)

bend radius: 75 / 100 / 150 / 200

weight: 0.93 kg/m

free carrying length: 2.0 m at 1.0 kg/m load



pitch: 45

order example:

Kolibri 40.062.5 / 100 x 1260

type / radius x length





Kolibri HEIGHT 40

inner height 31, inner width 48 to 60

Kolibri 40.075.2

rigid type
flap stay in inner radius
integrated connectors

space (axb): 29 x 60 separable (PZ ANr.1521)
bend radius: 60 / 75 / 100 / 150 / 200
weight: 1.05 kg/m
free carrying length: 2.0 m at 1.0 kg/m load
pitch: 45

order example:

Kolibri 40.075.2 / 100 x 1260

type / radius x length



Kolibri 40.075.6


rigid type
flap stay in outer radius
integrated connectors

space (axb): 29 x 60 separable (PZ ANr.1521)
bend radius: 60 / 75 / 100 / 150 / 200
weight: 1.05 kg/m
free carrying length: 2.0 m at 1.0 kg/m load
pitch: 45

order example:

Kolibri 40.075.6 / 100 x 1260

type / radius x length



Kolibri 40.112.7

telescopic type
PKK stay in inner radius
separate connector

space (axb): 31x100 separable (PZ ANr.2035)
bend radius: 55 / 100 / 150 / 200 / 230
weight: 0,9 kg/m
free carrying length: 2,5 at 1,0 kg/m load
pitch: 37

order example:

Kolibri 40.112.7 / 55 x 1295 / 100

type / radius x length / stay length



stay length 50 up to 100

Kolibri HEIGHT 50

inner height 38 to 40, inner width 48 to 134



Kolibri 50.065.0

standard type

flap stay in inner radius

integrated connectors

space (axb): 40 x 48 separable (PZ ANr.1113)

bend radius: 75 / 100 / 125 / 150 / 200 / 250

weight: 1.30 kg/m

free carrying: 2.4 m at 1.0 kg/m load

pitch: 55

order example:

Kolibri 50.065.0 / 100 x 1265

type / radius x length



Kolibri 50.065.5

colsed type

flap covers in outer radius

integrated connectors

space (axb): 40 x 48 separable (PZ ANr.1113)

bend radius: 100 / 150 / 200 / 250

weight: 1.30 kg/m

free carrying length: 2.4 m at 1.0 kg/m load

pitch: 55

order example:

Kolibri 50.065.5 / 100 x 1265

type / radius x length



Kolibri 50.095.0 50.095.1

standard type

flap stay in inner radius flap stay in outer radius

integrated connectors

space (axb): 40 x 78 separable (PZ ANr.1113)

bend radius: 75/100/ 125/ 150/ 175/ 200/ 250

weight: 1.35 kg/m


free carrying length: 2.4 m at 1.0 kg/m load

pitch: 55

order example:

Kolibri 50.095.0 / 100 x 1265

type / radius x length



Kolibri 50.095.2

rigid type

flap stay in inner radius

integrated connectors

space (axb): 38 x 78 separable (PZ ANr.1451)

bend radius: 75/100/ 125/ 150/ 175/ 200/ 250

weight: 1.40 kg/m


free carrying length: 2.4 m at 1.0 kg/m load

pitch: 55

order example:

Kolibri 50.095.2 / 100 x 1265

type / radius x length



Kolibri HEIGHT 50

inner height 38 to 40, inner width 48 to 134

Kolibri 50.095.5

closed type
flap stay in outer radius
integrated connectors

space (axb): 40 x 78 separable (PZ ANr.1113)
bend radius: 100/ 125/ 150/ 175/ 200/ 250
weight: 1.40 kg/m
free carrying length: 2.4 m at 1.0 kg/m load
pitch: 55

order example:

Kolibri 50.095.5 / 100 x 1265

type / radius x length

Kolibri 50.125.0

50.125.1

standard type
flap stay in inner radius
Integrated connectors

flap stay in outer radius

space (axb): 40 x 108 separable (PZ ANr.1326)
bend radius: 75 / 100 / 125 / 150 / 200 / 250
weight: 1.52 kg/m
free carrying length: 2.4 m at 1.0 kg/m load
pitch: 55

order example:

Kolibri 50.125.0 / 100 x 1265

type / radius x length

Kolibri 50.150.0

50.150.1

standard type
flap stay in inner radius
integrated connectors

flap stay in outer radius

space (axb): 40 x 133 separable (PZ ANr.1326)
bend radius: 75 / 100 / 150 / 200 / 250
weight: 1.90 kg/m
free carrying length: 2.4 m at 1.0 kg/m load
pitch: 55

order example:

Kolibri 50.150.0 / 100 x 1265

type / radius x length

Kolibri 50.150.5

closed type
flap stay in outer radius
integrated connectors

space (axb): 40 x 133 separable (PZ ANr.1113)
Bibend radius: 75 / 100 / 150 / 200 / 250
weight: 1.90 kg/m
free carrying length: 2.4 m at 1.0 kg/m load
pitch: 55

order example:

Kolibri 50.150.5 / 100 x 1265

type / radius x length

Kolibri HEIGHT 65

inner height 50, inner width 77 to 205



ekdgelenkro
energy drag chains

Kolibri 65.095.1

open type

flap stay in outer radius

integrated connectors

space (axb): 50 x 77 separable (PZ ANr.1129)

bend radius: 125 / 150 / 200 / 300

weight: 2.2 kg/m

free carrying length: 2.75 m at 1.0 kg/m load

pitch: 70

order example:

Kolibri 65.095.1 / 100 x 1400

type / radius x length



Kolibri 65.095.5

closed type

flap cover in outer radius

integrated connectors

space (axb): 50 x 77 separable (PZ ANr.1129)

bend radius: 125 / 150 / 200 / 300

weight: 2.2 kg/m

free carrying length: 2.75 m at 1.0 kg/m load

pitch: 70

order example:

Kolibri 65.095.5 / 100 x 1400

type / radius x length



Kolibri 65.135.1

open type

flap stay in outer radius

integrated connectors

space (axb): 50 x 117 separable (PZ ANr.1129)

bend radius: 125 / 150 / 200 / 300 / 400

weight: 2.6 kg/m

free carrying length: 2.75 m at 1.0 kg/m load

pitch: 70

order example:

Kolibri 65.135.1 / 100 x 1400

type / radius x length



Kolibri 65.135.5

closed type

flap cover in outer radius

integrated connectors

space (axb): 50 x 117 separable (PZ ANr.1129)

bend radius: 125 / 150 / 200 / 300 / 400

weight: 2.7 kg/m

free carrying length: 2.75 m at 1.0 kg/m load

pitch: 70

order example:

Kolibri 65.135.1 / 100 x 1400

type / radius x length



Kolibri HEIGHT 65

inner height 50, inner width 77 to 205



Kolibri 65.195.1

open type

flap stay in outer radius

integrated connectors

space (axb): 50 x 177 separable (PZ ANr.1129)

bend radius: 125 / 150 / 200 / 300

weight: 2.9 kg/m

free carrying length: 2.75 m at 1.0 kg/m load

pitch: 70

order example:

Kolibri 65.195.1 / 100 x 1400

type / radius x length



Kolibri 65.195.5

closed type

flap cover in outer radius

integrated connectors

space (axb): 50 x 177 separable (PZ ANr.1129)

bend radius: 125 / 150 / 200 / 300

weight: 3.0 kg/m

free carrying length: 2.75 m at 1.0 kg/m load

pitch: 70


order example:

Kolibri 65.195.5 / 100 x 1400


type / radius x length

Pos. name

- 1 link (open type)
- 2 link (closed type)
- 3 flange pivot
- 4 flange drilling
- 5 horn stay connector
- 6 horn stay 65 HS65
- 7 horn stay 85 HS 85
- 8 damping element
- 9 PZ (divider)
- 10 PZ (pinch stay)
- 11 flap stay
- 12 flap cover
- 13 notched horizontal divider
- 14 notched horiz. divider flying
- 15 telescopic horizontal divider
- 16 telescopic horiz. divider flying
- 17 ladderstay
- 20 connector 10.012.4 hole
- 21 connector 10.012.4 pivot



Opening and closing



Push a screwdriver as shown in the the slot (1) then with a light lever movement (2) raise the tongue and push the locking pins of the flap stay (or the flap cover) out of the drilling. The flap stay can then be lifted (3). To remove the flap stay the second side has to be unlocked and the stay has to be pushed out against the direction of the cones.

The installation of the flap stays and flap covers are snapped in a slight angle with the pins against the corresponding drillings (4) and with slight pressure against the locking tongue.


Lifted flap stays can be re-engaged (5) with slight pressure.

Lengthening and shortening

To lengthen or shorten the flap stays have to be opened. The walls with pivot pins are to press internally (1) and the walls with the holes are to press toward the outside (2). The chain links can be pushed together (3), or be pulled apart.

Installation of the flap stays


The assembly of the flap stays can take place before or after cable lining. Therefore energy chain does not need to be opened. The flap stays are inserted from the outside chain link floor until snap (1), (2). The dismantling of the stays is done by unlocking the tongue and pushing out (3).



Assembly of horizontal dividers

The horizontal dividers (notched, telescopic and ladder-stay) are horizontally slid onto the vertical dividers (PZ) (1).


With a screwdriver the locking tongue can be mounted (2) and horizontal dividers disassembled (3).



Mounting the energy chain and strain relief

Before mounting the energy chain horn stays may be assembled which can be used to fix the lines via cable ties. For most applications variable strain relief is recommended, to mount the anchor profile with the energy chain using the integrated connector. (1), (2).


It is also possible to attach the anchor profile as a separate strain relief. The anchor profile is suitable for various strain relief components (see design guidelines).



Snap assembly

The energy chain may be assembled with only one click using the Snap connector.

Horn stays will be clipped at the stays as strain relief elements. After that the energy chain can be clicked in the designated position.




Alternatively, it is possible to mount the cable chains with flush mounting flange type brackets (1).


Maintenance of the energy chain

Kolibri energy chains are maintenance free. Like every mechanical system there will - depending on the ambient conditions - wear which must be observed.


In case of this the energy chainspace has to be exchanged.



Kolibri 15.036.5
(Kolibri 02.5)




Kolibri 22.038.0
(Kolibri 05.0)



Kolibri 22.060.5
(Kolibri 07.5)

Kolibri 30.050.0
(Kolibri 10.0)




Kolibri 30.060.0
(Kolibri 11.0)


Kolibri 30.080.0
(Kolibri 12.0)

Kolibri 30.095.0
(Kolibri 13.0)

Kolibri 30.125.0
(Kolibri 14.0)




Kolibri 30.050.5
(Kolibri 10.5)





Kolibri 30.080.5
(Kolibri 12.5)

Kolibri 40.062.2
(Kolibri 15.2)

Kolibri 40.062.5
(Kolibri 15.5)





Kolibri parts 39



<i>Kolibri</i>	00.000.0				00.000.1				00.000.2 / .6				00.000.3	00.000.4	00.000.5		00.000.7	
	piece goods				(10m-coil)													
<i>Radius</i>	15	17.5	20	30	35	40	50	60	70	75	100	125	150	175	200	250	300	400
10.012.4 (00.3)	1089	-	-	1090	-	-	1091	-	-	-	-	-	-	-	-	-	-	-
13.023.4	-	-	-	-	2164	-	-	-	-	-	-	-	-	-	-	-	-	-
13.023.4	-	2137	-	-	2138	-	2139 (R55)	-	2140 (R80)	-	2141	-	-	-	-	-	-	-
15.015.3 (0)	-	1056	0435	0029	-	-	-	-	-	-	-	-	-	-	-	-	-	-
15.015.4 (0.3)	-	-	1116	1060	-	-	-	-	-	-	-	-	-	-	-	-	-	-
15.036.5 (02.5)	-	-	-	1156	-	-	1157	-	-	-	-	-	-	-	-	-	-	-
15.037.3 (02)	-	-	2191 ¹⁾	1983	-	-	-	-	-	-	-	-	-	-	-	-	-	-
15.051.0 (03)	-	-	0844	0845	-	-	-	-	-	-	-	-	-	-	-	-	-	-
22.025.4 (04.3)	-	-	-	-	0981	-	-	-	0982	-	0983	-	-	-	-	-	-	-
22.038.0 (05.0)	-	-	-	-	1686	-	1685	2133	1684	-	1683	-	-	-	-	-	-	-
22.048.0 (06)	-	-	-	-	0840	-	-	-	0841	-	-	-	-	-	-	-	-	-
22.060.5 (07.5)	-	-	-	-	-	-	1259	-	1260	-	1261	-	-	-	-	-	-	-
30.030.3 (1)	-	-	-	-	-	0457	-	-	-	-	0004	-	-	-	0005	-	-	-
30.060.3 (2)	-	-	-	-	-	0006	-	-	-	-	0007	-	0615	-	0008	-	-	-
30.050.0 (10.0)	-	-	-	-	-	1224	-	1430	-	1225	1222	-	1226	-	1223	-	-	-
30.050.1 (10.1)	-	-	-	-	-	-	-	-	-	1835	1748	-	-	-	-	-	-	-
30.050.5 (10.5)	-	-	-	-	-	-	-	1002	-	1010	1003	-	1011	-	1004	-	-	-
30.060.0 (11.0)	-	-	-	-	-	1229	1377	-	-	1230	1227	-	1231	-	1228	-	-	-
30.060.1 (11.1)	-	-	-	-	-	-	-	-	-	1944	1750	-	-	-	-	-	-	-
30.080.0 (12.0)	-	-	-	-	-	1235	-	-	-	1236	1232	-	1233	-	1234	-	-	-
30.080.1 (12.2)	-	-	-	-	-	-	-	-	-	1394	1621	-	-	-	-	-	-	-
30.080.2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
30.080.4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
30.080.5 (12.5)	-	-	-	-	-	-	-	1798	-	-	1795	-	1796	-	1797	-	-	-
30.095.0 (13.0)	-	-	-	-	-	1239	-	-	-	1240	1237	1324	1241	-	1238	-	-	-
30.095.1 (13.1)	-	-	-	-	-	1992	-	-	-	1411	1645	1993	1994	-	1995	-	-	-
30.125.0 (14.0)	-	-	-	-	-	1245	-	-	-	1246	1242	-	1243	-	1244	-	-	-
30.125.1 (14.0)	-	-	-	-	-	1973	-	-	-	1974	1975	-	-	-	-	-	-	-
40.062.2 (15.0)	-	-	-	-	-	-	-	1489	-	1490	1491	-	1492	-	1493	-	-	-
40.062.5 (15.5)	-	-	-	-	-	-	-	-	-	1152	1163	-	1154	-	1155	-	-	-
40.075.2 (16.0)	-	-	-	-	-	-	-	1484	-	1485	1486	-	1487	-	1488	-	-	-
40.075.6	-	-	-	-	-	-	-	2056	-	2055	2054	-	2053	-	2052	-	-	-
40.112.7	-	-	-	-	-	-	-	2030/2031 (R55)	-	-	-	-	-	-	-	-	-	-
50.065.0 (21.0)	-	-	-	-	-	-	-	-	-	0971	0972	1256	0973	-	0974	0975	-	-
50.065.5 (21.5)	-	-	-	-	-	-	-	-	-	-	1005	-	1006	-	1007	1008	-	-
50.095.0 (19.0)	-	-	-	-	-	-	-	-	-	1138	1148	1431	1139	1325	1140	1141	-	-
50.095.1 (19.1)	-	-	-	-	-	-	-	-	-	1947	1948	1949	1950	1951	1952	2016	-	-
50.095.2 (19.2)	-	-	-	-	-	-	-	-	-	1619	1644	1483	1370	-	-	-	-	-
50.095.5 (19.5)	-	-	-	-	-	-	-	-	-	-	1012	-	1013	-	1014	1016	-	-
50.125.0 (22.0)	-	-	-	-	-	-	-	-	-	1292	1288	2158	1289	-	1290	1291	-	-
50.150.0 (20.0)	-	-	-	-	-	-	-	-	-	1287	1283	-	1284	-	1285	1286	-	-
50.150.5 (20.5)	-	-	-	-	-	-	-	-	-	-	1061	-	1062	-	1063	1064	-	-
65.095.1 (24.1)	-	-	-	-	-	-	-	-	-	-	-	1252	1253	-	1254	-	1255	-
65.095.5 (24.5)	-	-	-	-	-	-	-	-	-	-	-	1084	1085	-	1086	-	1087	-
65.135.1 (25.1)	-	-	-	-	-	-	-	-	-	-	-	1753	1754	-	1755	-	1756	1757
65.135.5 (25.5)	-	-	-	-	-	-	-	-	-	-	-	1076	1077	-	1078	-	1079	1752
65.195.1 (27.1)	-	-	-	-	-	-	-	-	-	-	-	1758	1922	-	1759	-	1760	-
65.195.5 (27.5)	-	-	-	-	-	-	-	-	-	-	-	1080	1081	-	1082	-	1083	-


¹⁾ R24

ekd gelenkrohr
energy drag chains

Kolibri parts 39

[illegible]

Kolibri parts 39



Kolibri	FK	notched hor. divider flying	ladderstay	PTF flying	PT 55 55-80	PT 75 75-100	head	side	flange
10.012.4	-	-	-	-	-	-	-	-	1576
13.023.4	-	-	-	-	-	-	-	-	
13.023.4	-	-	-	-	-	-	-	-	
15.015.3	-	-	-	-	-	-	-	-	
15.015.4	-	-	-	-	-	-	-	-	
15.036.5	-	-	-	-	-	-	1339	-	
15.037.3	-	-	-	-	-	-	-	-	
15.051.0	-	-	-	-	-	-	-	-	
22.025.4	-	-	-	-	-	-	-	-	
22.038.0	-	-	-	-	-	-	1745	-	
22.048.0	-	-	-	-	-	-	-	-	
22.060.5	-	1127	-	-	-	-	1340	-	
30.030.3	-	-	-	-	-	-	-	-	
30.060.3	-	-	-	-	-	-	-	-	
30.050.0	1363	-	-	-	-	-	1329	-	
30.050.1	1363	-	-	-	-	-	1329	-	
30.050.5	1363	1127	-	-	-	-	1341	-	
30.060.0	1363	-	-	-	-	-	1330	-	
30.060.1	1363	-	-	-	-	-	1330	-	
30.080.0	1363	-	-	-	-	-	1331	-	
30.080.1	1363	-	-	-	-	-	1331	-	
30.080.2	1363	-	-	1665	1927	-	-	-	
30.080.4	1363	-	-	-	-	-	1331	-	
30.080.5	1363	1127	-	-	-	-	-	-	
30.095.0	1363	-	-	-	-	-	1332	-	
30.095.1	1363	-	-	-	-	-	1332	-	
30.125.0	1363	-	-	-	-	-	1333	-	
30.125.1	1363	-	-	-	-	-	1333	-	
40.062.2	1363	-	-	1665	1927	-	1996 / 1997	-	
40.062.5	1363	-	-	-	-	-	1343	-	
40.075.2	1363	-	-	1665	1927	-	-	-	
40.075.6	1363	-	-	1665	1927	-	-	-	
40.112.7	-	-	-	-	-	-	2037 / 2036	-	2038
50.065.0	1269	1127	-	-	-	-	1336	-	
50.065.5	1269	1127	-	-	-	-	1346	-	
50.095.0	1269	1127	1127	-	-	-	1334	-	
50.095.1	1269	1127	1127	-	-	-	1334	-	
50.095.2	1269	-	-	1665	1927	-	-	-	
50.095.5	1269	1127	1127	-	-	-	1344	-	
50.125.0	1269	-	-	-	-	-	1337	-	
50.150.0	1269	-	-	-	-	-	1335	-	
50.150.5	1269	1127	1127	-	-	-	1345	-	
65.095.1	1269	-	-	1665	1927	-	1347	-	
65.095.5	1269	-	-	1665	1927	-	1347	-	
65.135.1	1269	-	-	1665	1927	0879 0880	1348	-	
65.135.5	1269	-	-	1665	1927	0879 0880	1348	-	
65.195.1	1269	-	-	1665	1927	0879 0880	1349	-	
65.195.5	1269	-	-	1665	1927	0879 0880	1349	-	

Kolibri PART NUMBERS



special material parts like UI94 V-0, EX or other have to be named in the order



Kolibri anchor profile ZL50 blue ribbon ZLA 8 (PZ SLP220) ZHS10 ZLS10 HS55 HS65 HS75 HS85

10.012.4	-	-	-	-	-	-	-	-	-	-	-
13.023.4	-	-	-	-	-	-	-	-	-	-	-
13.023.4	-	-	-	-	-	-	-	-	-	-	-
15.015.3	-	-	-	-	-	-	-	-	-	-	-
15.015.4	-	-	-	-	-	-	-	-	-	-	-
15.036.5	-	-	-	-	-	-	-	-	-	-	-
15.037.3	-	-	-	-	-	-	-	-	-	-	-
15.051.0	-	-	-	-	-	-	-	-	-	-	-
22.025.4	1163	-	1142	1159	0778	1407	1160	-	-	-	-
22.038.0	1163	-	1142	1159	0778	1407	1160	-	-	-	-
22.048.0	1163	-	1142	1159	0778	1407	1160	-	-	-	-
22.060.5	1163	-	1142	1159	0778	1407	1160	-	-	-	-
30.030.3	1163	-	1142	1159	0778	1407	1160	-	-	-	-
30.060.3	1163	-	1142	1159	0778	1407	1160	-	-	-	-
30.050.0	1163	-	1142	1159	0778	1407	1160	1802	-	-	-
30.050.1	1163	-	1142	1159	0778	1407	1160	1802	-	-	-
30.050.5	1163	-	1142	1159	0778	1407	1160	-	-	-	-
30.060.0	1163	-	1142	1159	0778	1407	1160	1802	-	-	-
30.060.1	1163	-	1142	1159	0778	1407	1160	1802	-	-	-
30.080.0	1163	-	1142	1159	0778	1407	1160	1802	1503 ¹⁾	-	1812 ¹⁾
30.080.1	1163	-	1142	1159	0778	1407	1160	1802	1503 ¹⁾	-	1812 ¹⁾
30.080.2	1163	-	1142	1159	0778	1407	1160	-	1503	-	1812
30.080.4	1163	-	1142	1159	0778	1407	1160	-	1503	-	1812
30.080.5	1163	-	1142	1159	0778	1407	1160	-	-	-	-
30.095.0	1163	-	1142	1159	0778	1407	1160	1802	-	-	-
30.095.1	1163	-	1142	1159	0778	1407	1160	1802	-	-	-
30.125.0	1163	-	1142	1159	0778	1407	1160	1802	-	-	-
30.125.1	1163	-	1142	1159	0778	1407	1160	1802	-	-	-
40.062.2	1163	-	1142	1159	0778	1407	1160	-	1503	-	1812
40.062.5	1163	-	1142	1159	0778	1407	1160	-	-	-	-
40.075.2	1163	-	1142	1159	0778	1407	1160	-	1503	-	1812
40.075.2	1163	-	1142	1159	0778	1407	1160	-	1503	-	1812
40.112.7	1163	-	-	1159	0778	1407	1160	-	-	-	-
50.065.0	1163	1273	1142	1159	-	1407	1160	-	-	-	-
50.065.5	1163	1273	1142	1159	-	1407	1160	-	-	-	-
50.095.0	1163	1273	1142	1159	-	1407	1160	-	1503 ¹⁾	1504	1812 ¹⁾
50.095.1	1163	1273	1142	1159	-	1407	1160	-	1503 ¹⁾	1504	1812 ¹⁾
50.095.2	1163	1273	1142	1159	-	1407	1160	-	1503	-	1812
50.095.5	1163	1273	1142	1159	-	1407	1160	-	-	-	-
50.125.0	1163	1273	1142	1159	-	1407	1160	-	-	1504	-
50.150.0	1163	1273	1142	1159	-	1407	1160	-	-	1504	-
50.150.5	1163	1273	1142	1159	-	1407	1160	-	-	-	-
65.095.1	1163	1273	1142	1159	-	1407	1160	-	-	-	-
65.095.5	1163	1273	1142	1159	-	1407	1160	-	-	-	-
65.135.1	1163	1273	1142	1159	-	1407	1160	-	-	-	-
65.135.5	1163	1273	1142	1159	-	1407	1160	-	-	-	-
65.195.1	1163	1273	1142	1159	-	1407	1160	-	-	-	-
65.195.5	1163	1273	1142	1159	-	1407	1160	-	-	-	-

¹⁾ with horn stay connectors